




## MHO-H411

### Mini 3-in-1 Portable CO2 Detector

Get Real-Time Environmental Data on  
Your Desktop



**Above 1500 ppm**  
Unable to work actively

**801 - 1500 ppm**  
Mentally tired

**400 - 800 ppm**  
Good office environment

Tri-color LED Indicator

### 14-day Long Battery Life

Support Type-C charging, rechargeable carp battery 500mAh. Fully charged sustainable working 14 days.



Bluetooth Connection

### Portable Sleek Design

With a lightweight design and palm-sized, the product can be easily applied in a variety of scenarios.



Ultra Light & Minimal Design

### 197 ft Whole-Room Coverage

Up to 60m/197ft enabled range allows you to clearly understand your home environment on the MEAWOW app. Easily hold the data in the palm of your hand.



CO2 Monitoring



Temperature Monitoring



Humidity Monitoring



Swiss-Made Sensor



°C/°F Switchable



14-day Battery Life



Palm Size



Easy to Read

#### Product Information

Size:  
50 x 50 x 16.3mm

Material:  
PC/ABS

Screen:  
LCD segment screen, 33.4x33.4mm (VA)

LED Indicator:  
Green (400-800ppm), Yellow (800-1500ppm), Red (1500-5000ppm)

Press Button:  
On/Off, Switch mode (double click/click), Restore default settings (long press for 12 seconds)

Wireless Connection:  
BLE

Battery type:  
Rechargeable lithium battery 500mAh

Power Interface:  
USB type-C

Battery Life:  
14-days Battery Life (Calculated based on 8 hours of continuous detection and LED indicator off each day)

Detection Mode:  
Continuous Detection, One-time Detection

Co2 Detection Frequency:  
Continuous detection per 30 seconds; one-time detection per 5 seconds

Co2 Detection Range:  
400-5000ppm

Co2 Detection Accuracy:  
± 50 ppm +5% of reading

Temperature Detection Range:  
0-60 C

Temperature Accuracy:  
±1 C

Humidity Measurement Range:  
0-99%RH

Humidity Accuracy:  
±10%RH (10-90%RH)

Operating Temperature And Humidity Range:  
0-60 C, 10-95%RH

Storage Temperature Range:  
-40-70 C